

Thermal Labeller



Specifications:

▶ Printing:

- ✓ Thermal transfer or direct thermal printing method
- ✓ Standard ribbon rewinder
- ✓ Printing resolution 203 dpi (8 dots/mm)
- ✓ Print speed up to 127 mm/sec
- ✓ Maximum print length 1016 mm
- ✓ Maximum print width 108 mm

▶ Labelling:

- ✓ Label length from 10 mm up to 999 mm
- ✓ Label width from 20 mm up to 112 mm
- ✓ Label thickness from 0.06 mm up to 0.19 mm
- ✓ Label roll dimensions 127 mm OD (5.0" OD)
- ✓ 8 fixed alphanumeric fonts, 1 true type font with rotation at 0, 90, 180 and 270 degrees
- ✓ Bar Codes = Code 39, 39C, 93, 128uCC, 128(Subset A, B, C), Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN e UPC 2(5) digits add-on, MSI, PLESSEY, POSNET, China Post, ITF 14, EAN 14
- ✓ 2D Bar Codes = PDF-417, MAXICODE, DATA MATRIX, QR code

▶ Dimensions:

- ✓ 314 l x 213 w x 188 h mm

▶ Technical Features:

- ✓ Memory 2 MB DRAM, 2 MB Flash Memory
- ✓ RS 232, Parallel, USB 1.1 interfaces
- ✓ Standard software programming for the creation of customised labels with logos, images, weight data and bar codes
- ✓ Switching 100/240 VAC, 24V 3.75 A DC (external power adapter)
- ✓ From 5 to 40°C operating temperature

John White & Son (Weighing Machines) Ltd

6 Back Dykes – Auchtermuchty – Fife - KY14 7DW

Contact us

T: +44 (0)1337 827600

F: +44 (0)1337 827444

enquiries@johnwhiteandson.com



www.johnwhiteandson.com

